

GSM/GPRS Data Module

TM2Q



TM2Q is surface mount module with QFN type pins.

TM2Q is a low power consumption, quad band, GSM/GPRS class 10 data module with speech capability.

Main TM2Q Applications are Automotive (Telematics, and Car Security) and M2M (Automation, Real Time Data Transmission, Remote Metering and Control, Surveillance and Security).

FEATURES:

- Supplementary functionality to meet the user's requirements:
 - o Integrated TCP/IP Stack.
 - o Read/Save Flash data.
 - o GPIO controlling.
- Supplementary GSM features:
 - o CSD.
 - o SMS (text/data).
- Quad-Band GSM 850 / 900 / 1800 / 1900 MHz.
- Output power:
 - o class 4 (2 W) for EGSM 850/900.
 - o class 1 (1 W) for GSM 1800/1900.
- Weight: < 10 g.
- Supply voltage range: 3.5 ... 4.2 V (Typ: 3.8 +/- 0.2 V).
- Ambient temperature: -20 °C...+55 °C.
- Dimensions:
 - o 34.4 mm x 32.5 mm x 3.6 mm

- Power consumption:
 - Idle : < 2 mA.
 - In call (GSM pwr. lev. 5): 300 mA.
- Interfaces:
 - 2 serial ports.
- I2C bus, SPI bus, 2 x analog in (ADC)*
- 12 GPIOs
- GSM/GPRS protocol stack release 99.
- Subset of GSM 07.05, GSM 07.07 and proprietary AT commands.
- SIM application toolkit (SAT Release 99).
- Fax: Group 3, class 2.0.
- GPRS multi slot class 10.
 - Full PBCCH support.
 - MS class B.
 - Coding scheme 1- 4.
- Circuit Switched Data: Up to 9.6 kbit/s, Transparent/Non-transparent mode.
- Supplementary Services.
- SMS: Via GSM or GPRS, Point-to-point MO and MT, Text and PDU mode.
- SMS cell broadcast.
- Voice:
 - HR, FR, EFR and AMR.
 - Basic hands-free.
 - Echo cancellation.



GSM/GPRS Data Module

TM2Q

* Accessible via M2M application on client's request. This can be done by Teltonika.

mobile[solutions]

Official distributor in Switzerland

mobile solutions ag
im schörli 1, 8600 dübendorf
phone: +41 44 802 44 88
fax: +41 44 802 44 99
modules@mobilesolutions.ch
www.mobilesolutions.ch